


3001

Manicotto - Coupler - Manchon - Manguito - Muffe - Μύφτα

PE100RC - S5 Gas - PN 16 20°C



PE100 - SDR11 - S5

ACQUA: PFA (PN)=16 bar 20°C

GAS: MOP=10 bar; In Italia MOP=5 bar (D.M. 24/11/84, D.M. 16/4/2008 e successive modifiche)

Per il tempo di saldatura da utilizzare con tubo SDR26 contattare direttamente Unidelta.

PE100 - SDR11 - S5

WATER: PFA (PN)=16 bar 20°C

GAS: MOP=10 bar; in Italy MOP=5 bar (D.M. 24/11/84, D.M. 16/4/2008 and further modification)

Contact Unidelta directly for the welding time to be used with SDR26 pipe.

DIM dxd [mm]	CODE	DIM MAX LxHxP [mm]	L [mm]	H [mm]	W-SDR	PACK [UMV]			
						RIF. 10	RIF. 11	RIF. 12	RIF. 2
25x25	3001026000001	75x55x36	75	55	≤ 11	-	45	-	-
32x32	3001033000001	76x62x44	76	62	≤ 11	-	30	-	-
40x40	3001041000001	80x71x54	80	71	≤ 17	-	20	-	-
50x50	3001051000001	88x82x65	88	82	≤ 17	-	16	-	-

5007

Flussimetro da 1" - Flow control 1" - Fluxmètre de 1" - Caudalimetro de 1" - Durchgangsmesser 1" - Контролер потока 1"



DIM [in.]	CODE	DESCRIZIONE - DESCRIPTION
1" M x 1" M	5507000000001	Portata 8 - 38 l/min

60010227

Valvola a sfera dritta maschio-femmina completa di bocchettone a tenuta morbida, manovra a farfalla (rossa) - Male-female straight ball valve complete with soft-seal fitting, butterfly operation (red) - Vanne à bille droite mâle-femelle avec goulotte à étanchéité souple, manoeuvre à papillon (rouge) - Válvula de bola recta macho-hembra completa de manguito de unión con junta blanda, vuelta a mariposa para maniobrar (roja) - Kugelhahn Außergewinde/Innengewinde, komplett mit weichdichtender Verschraubung, Klappenbetätigung (rot) - Кран шаровой ВР/НР, ручка бабочка (красный цвет)



CODE	PACK [UMV]
	Sfusi - Loose
6001022701001	1