


## RIV 2500

"Y" Strainer F/F


### Tech drawings and tables



DN	Code	h	S	F	PN	KG	P/box
1/2"	032500000004	38	56	11	16	0,168	20
3/4"	032500000005	50	70	11	16	0,253	20
1"	032500000007	59	88	15	16	0,417	10
1"1/4	032500000008	68	96	15	16	0,648	10
1"1/2	032500000009	77	106	16	16	0,834	5
2"	032500000011	93	126	19	16	1,309	2
2"1/2	032500000013	99	133	21	16	2,277	1
3"	032500000014	132	170	22	16	3,237	1
4"	032500000016	170	219	25	16	5,429	1

## Technical data

Art. 2500



Materials			
1	Body	Brass	1/2" - 1"1/4 CW617N 1"1/2 - 4" CB754S
2	Filter	Stainless Steel	AISI 304
3	Gasket	NBR	
4	Plug	Brass	CW617N

Connections	ISO 228/1
Limit	-10°C (without liquid) +90°C
Notes	The max. working pressure (PN) means at a room temperature of about 23°C.

## Kv & Cv Coefficients

Size	Kv	Cv
1/2"	4,6	-
3/4"	7,8	-
1"	11,2	-
1"1/4	16,1	-
1"1/2	22,5	-
2"	27,0	-
2"1/2	32,0	-
3"	57,0	-
4"	95,0	-