




RIV 3450

Reducer M/F


Tech drawings and tables



DNxDN1	Code	H	F	PN	KG	P/box
1/4" x 1/8"	033450000118	14	9	10	0,010	50
3/8" x 1/8"	033450000144	15	10	10	0,021	50
3/8" x 1/4"	033450000145	15	10	10	0,014	50
1/2" x 1/4"	033450000181	17	10	10	0,037	30
1/2" x 3/8"	033450000182	16	10	10	0,018	50
3/4" x 1/4"	033450000225	19	12	10	0,068	20
3/4" x 3/8"	033450000226	19	12	10	0,054	20
3/4" x 1/2"	033450000227	18	12	10	0,037	50
1" x 3/8"	033450000267	25	18,5	10	0,103	20
1" x 1/2"	033450000268	21	13	10	0,097	20
1" x 3/4"	033450000269	21	13	10	0,152	25
1"1/4 x 3/4"	033450000308	28,5	21	10	0,149	10
1"1/4 x 1"	033450000310	24	16	10	0,120	15
1"1/2 x 3/4"	033450000344	33	24	10	0,326	6
1"1/2 x 1"	033450000346	33	24	10	0,282	6
1"1/2 x 1"1/4	033450000347	35	25	10	0,184	8
2" x 1"1/4	033450000388	35,5	25,5	10	0,265	4
2" x 1"1/2	033450000389	36	25,5	10	0,284	4
2"1/2 x 2"	033450000434	34	25,5	10	0,224	4

Technical data

Art. 3400



Materials

1 Body Brass CW617N

Connections

ISO 228/1

Limit

-10°C (without liquid) +100°C

Notes

The max. working pressure (PN) means at a room temperature of about 23°C.