




## RIV 7226

Ball valve M/F for rising pipe  
 full bore  
 (EN 331 MOP 5-20)  
 tamperproof brass sealing safety cap and plastic sealing cover cap

### Tech drawings and tables




DN	Code	Ø	H	S	F	CH	PN	KG	P/box
1/2"	077226000004	15	51	66	16	25	5	0,22	10
3/4"	077226000005	20	57	76	17,5	31	5	0,34	10
1"	077226000007	25	61	91	21	38	5	0,58	10
1"1/4	077226000008	32	74	101	22,5	47	5	0,97	6
1"1/2	077226000009	40	82	113	22,5	54,5	5	1,16	4
2"	077226000011	50	90	134	26,5	66	5	1,94	4

### Advantages

## Technical data

Art. 7160




### Materials


1	Body	Brass	CuZn40Pb2	Nickel-plated
2	Body end	Brass	CuZn40Pb2	Nickel-plated
3	Ball	Brass	CuZn40Pb2	Chrome-plated
4	Seats	P.T.F.E.		
5	O-Ring	FKM		
6	O-Ring	NBR		
7	Stem	Brass	CuZn39Pb3	
8	Lever	Aluminium	GD-AISI12Cu2Fe	Yellow
9	Screw	Steel		Zinc-plated

<b>Connections</b>	F/F: ISO 7/1Rp (parallel), ANSI B1.20.1 (NPT) - M/F: male ISO 7/1R (tapered), female ISO 7/1Rp (parallel)
<b>Limit</b>	-20 °+70 ° (without liquid)
<b>Notes</b>	The max.working pressure (PN) means at a room temperature of about 23°C.

## Pressure Loss Chart



## Temperature/Pressure



## Kv & Cv Coefficients

Size	Kv	Cv
1/4"	4,1	-
3/8"	6,3	-
1/2"	15,8	-
3/4"	29,0	-
1"	50,0	-
1"1/4	82,0	-
1"1/2	184,0	-
2"	340,0	-
2"1/2	580,0	-
3"	940,0	-
4"	1600,0	-

## Approvals



RIV Rubinetterie Italiane Velatta S.p.A. - Via delle Acacie, 8 Zona Industriale D4 - 28075 GRIGNASCO (NO) - ITALY  
Tel +39 0163 4151 Fax +39 0163 411914 E-mail riv-vg@riv-vg.com Web www.riv-vg.com

Capitale sociale € 516.000 i.v. - Reg. Imprese di Novara N° 00469610026 - R.E.A. di Novara N° 170397  
Numero Meccanografico NO009263 - Codice Fiscale: 00469610026 - Partita IVA: IT 01399720034



